ZEBRA TC75 MOBILE COMPUTER

TC75 RUGGED ANDROID TOUCH COMPUTER

7EPPA

Your front line to a smarter enterprise

Your field workforce needs a mobile computer to access the people and information required to maximize efficiency and better serve your customers. You want to give them an enterprise-class handheld built for life out in the field — yet your workers expect a device that is every bit as refined and easy-to-use as their own consumer smartphone. Introducing the TC75, the Android mobile computer that delivers it all. A rugged design that delivers reliable everyday operation. Anywhere anytime access to virtually any information in your back-end systems. The ability to capture more types of data faster than ever before. Instant push-to-talk communications with co-workers out in the field as well as supervisors, dispatch and more back in the office. Fast data access with support for all 4G GSM cellular networks. And a full complement of accessories meets the unique needs of virtually any mobile worker. The TC75 — the easy way to empower your field teams with a true mobile office.



Enterprise-class Android

KitKat Every TC75 ships with Mobility Extensions (Mx), a series of features that transform Android™ from a consumer operating system (OS) to a true enterprise-class OS, providing enterprise-class security and device management, as well as enterprise data capture capabilities.

Maximum data entry flexibility with an industry leading dual mode touch panel

Let your users choose their preferred data input pair: finger and gloved finger or finger and stylus — ideal for crisp signature capture. The intelligent 4.7 in display automatically adjusts as needed,

unlike competitive devices that require setting adjustments every time the user switches data input method.

World-class data capture

An integrated enterprise-class imager offers Zebra's proprietary PRZM Intelligent Imaging technology, a megapixel sensor and advanced optics, enabling the lightning-fast capture of 1D and 2D bar codes in virtually any condition. The 8 MP camera enables the easy capture of high-resolution photos, signatures, videos and more, so workers can capture more types of business intelligence to streamline more business processes. The front camera allows workers to place a video call to get the on-the-spot assistance they need. And Near Field Communications automates identity verification at facility entry points.

Automatically capture data and process entire documents

With SimulScan Document Capture, your workers can simultaneously capture bar codes, text fields, phone numbers, images, signatures and even check boxes in the time it takes to press a button, improving invoicing speed, order speed and more.

Superior audio quality and functionality for a new level of voice flexibility

Up to four times the loudness of popular smartphones and noise cancelling technology provides crystal clear audio on both ends of every call. Support for Workforce Connect Push-to-Talk (PTT) Express and Pro provides an instant connection to co-workers in the field, plus supervisors and other support staff back in the office.

Mobility DNA



Every strand of your mobility platform is simpler with Zebra's Mobility DNA. That's

because, from the start, you have the industry's most comprehensive suite of mobility must-haves to accelerate your solution. More off-the shelf end-user apps, more robust administration utilities and easier app development. Purpose built for enterprise, Mobility DNA makes ease, confidence and value intrinsic to your investment and our full line of Android mobile computers.

A robust accessory family for easy on-the-go device management

Accessories include a flexible vehicle cradle for charging — even with snapon accessories attached. A magnetic stripe reader enables mobile payment. The field attachable trigger handle brings comfort to scan intensive tasks. Select Zebra Bluetooth printers enable anywhere anytime printing. And backroom management is easier and more cost effective than ever thanks to our unique ShareCradle System that accommodates the TC75 and future Zebra mobile computers.

Rugged and ready for all-day every day use out in the field

The TC75 delivers reliable operation, even after multiple 8 ft./2.4 m drops to concrete and 2,000 consecutive 3.2 ft./1 m tumbles in our punishing tumble test. With IP67 sealing, the TC75 is dust-tight and can survive complete immersion in water. And the Corning Gorilla Glass touch panel and scanner exit window bring a new level of durability to two of the most vulnerable components on any handheld device.

Boost efficiency and customer service with the TC75 in:

T&L

- · Proof of delivery
- · Asset management
- Asset tracking
- Scheduling
- Routing
- · Location services

Field Service

- · Asset management
- Parts inventory
- Invoicing
- Task management
- · Location based services
- · Technical assistance
- Appointment scheduling
- Service automation

Direct Store Distribution (DSD)/Route Accounting

- Order automation
- Delivery tracking
- Inventory management
- Store setup
- Customer support

Government and Public Safety

- Alternate to two-way radio
- Data collection
- · Records query
- Real time data and voice
- ID validation / ticketing
- Location services
- Resource deployment
- Document on the scene video and photos

Specifications Chart

Meight 13.3 oz./376 g Display 4.7 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel Imager Window Corning Gorilla Glass Touchpanel Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass Backlight LED backlight Power PowerPrecision: Improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical; battery swap function Expansion Slot User accessible MicroSD up to 32GB SDHC and up to 64GB SDXC SIM 2 Nano SIM slot (4FF) 1 Mini SIM/SAM slot (2FF) Network Connections USB 2.0 High Speed (host and client); WLAN Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch volce; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating System Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating 4° F to 122° F/-20° C to 50°C per ML-STD 8108 Storage Temp. 4° F to 122° F/-20° C to 50°C per ML-STD 8108 Storage Temp. 4° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and	FITT SICAL CITA	RACTERISTICS
Display 4.7 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel Imager Window Corning Gorilla Glass Touchpanel Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass Backlight LED backlight Power PowerPrecision: Improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical; battery swap function Expansion Slot User accessible MicroSD up to 32GB SDHC and up to 64GB SDXC SIM 2 Nano SIM slot (4FF) 1 Mini SIM/SAM slot (2FF) Network Connections USB 2.0 High Speed (host and client); WLAN Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 4° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and	Dimensions	
exceptionally bright, outdoor viewable; optically bonded to touch panel Imager Window Corning Gorilla Glass Touchpanel Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass Backlight LED backlight Power PowerPrecision: Improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical; battery swap function Expansion Slot User accessible MicroSD up to 32GB SDHC and up to 64GB SDXC SIM 2 Nano SIM slot (4FF) 1 Mini SIM/SAM slot (2FF) Network Connections USB 2.0 High Speed (host and client); WLAN Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and	Weight	13.3 oz./376 g
Touchpanel Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass Backlight LED backlight Power PowerPrecision: Improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical; battery swap function Expansion Slot User accessible MicroSD up to 32GB SDHC and up to 64GB SDXC SIM 2 Nano SIM slot (4FF) 1 Mini SIM/SAM slot (2FF) Network Connections USB 2.0 High Speed (host and client); WLAN Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating System Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and	Display	exceptionally bright, outdoor view-
stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass Backlight LED backlight Power PowerPrecision: Improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management Li-Ion 3.7 V, 4620 mAh typical; battery swap function Expansion Slot User accessible MicroSD up to 32GB SDHC and up to 64GB SDXC SIM 2 Nano SIM slot (4FF) 1 Mini SIM/SAM slot (2FF) Network Connections USB 2.0 High Speed (host and client); WLAN Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 4° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Tomble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and turns over the operating temp, range	Imager Window	Corning Gorilla Glass
Power PowerPrecision: Improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical; battery swap function Expansion Slot User accessible MicroSD up to 32GB SDHC and up to 64GB SDXC SIM 2 Nano SIM slot (4FF) 1 Mini SIM/SAM slot (2FF) Network USB 2.0 High Speed (host and client); WLAN Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft/2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range	Touchpanel	stylus or bare or gloved fingertip input (conductive stylus sold sepa-
battery technology for longer cycle times and real-time visibility into battery metrics for better battery management Li-Ion 3.7 V, 4620 mAh typical; battery swap function Expansion Slot User accessible MicroSD up to 32GB SDHC and up to 64GB SDXC SIM 2 Nano SIM slot (4FF) 1 Mini SIM/SAM slot (2FF) Network Connections USB 2.0 High Speed (host and client); WLAN Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating System Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating Temp. 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range	Backlight	LED backlight
32GB SDHC and up to 64GB SDXC SIM 2 Nano SIM slot (4FF) 1 Mini SIM/SAM slot (2FF) Network Connections USB 2.0 High Speed (host and client); WLAN Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating System Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating Temp. 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and	Power	battery technology for longer cycle times and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh
Network Connections USB 2.0 High Speed (host and client); WLAN Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating System Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating Temp. 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range	Expansion Slot	
Connections client); WLAN Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range	SIM	. ,
LEDs; vibration Keypad On-screen keypad Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating System Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating Temp. 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 4° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and		
Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating System Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating Temp. 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 4° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft/2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and	Notification	
cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU 1.7 GHz dual core processor Operating System Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating Temp. 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and	Keypad	On-screen keypad
CPU 1.7 GHz dual core processor Operating System Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. 40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and	Voice and Audio	Bluetooth wireless headset support, High quality speaker phone with up to 108 db SPL volume; PTT headset support; Cellular circuit switch voice;
Operating System Android AOSP 4.4.3 with Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating Temp. 4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. -40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and	PERFORMANCI	E CHARACTERISTICS
Mobility Extensions (Mx), a layer of features that turns Android into a true enterprise-class OS Memory 1 GB RAM / 8 GB Flash pSLC USER ENVIRONMENT Operating	CPU	1.7 GHz dual core processor
USER ENVIRONMENT Operating Temp. -4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. -40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft/2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and		Mobility Extensions (Mx), a layer of features that turns Android
Operating Temp. -4° F to 122° F/-20° C to 50°C per MIL-STD 810B Storage Temp. -40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft/2.4 m to concrete at room temp.; 6 ft/1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft/1.0 m tumbles; meets and	Memory	1 GB RAM / 8 GB Flash pSLC
Temp. MIL-STD 810B Storage Temp. -40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Spec. 8 ft/2.4 m to concrete at room temp.; 6 ft/1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft/1.0 m tumbles; meets and	USER ENVIRON	IMENT
Humidity 5% to 85% non-condensing Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and		
Drop Spec. 8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and	Storage Temp.	-40° F to 158° F/-40° C to 70° C
6 ft./1.8 m over the operating temp. range Tumble Spec. 2,000 3.2 ft./1.0 m tumbles; meets and	Humidity	5% to 85% non-condensing
	Drop Spec.	8 ft./2.4 m to concrete at room temp.; 6 ft./1.8 m over the operating temp. range
	Tumble Spec.	2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC tumble specifications

USER ENVIRON	MENT (CONTINUED)
Sealing	IP67 per applicable IEC sealing specifications
Vibration	4 g's PK Sine (5 Hz to 2 kHz); 0.04g2/ Hz Random (20 Hz to 2 kHz); 60 minute duration per axis, 3 axis
Thermal Shock	-40° F to 158° F/-40° C to 70° C rapid transition
Electrostatic Discharge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge
COMMUNICATION AND MESSAGING	
Workforce Connect PTT Express (included) for instant PTT calls between workers inside the four walls; Workforce Connect PTT Pro (supported) for PTT calls and text messaging over Wi-Fi and cellular networks; Workforce Connec Voice client (supported) to enable PBX handset functionality and more inside the four walls.	
INTERACTIVE S	SENSOR TECHNOLOGY
Light Sensor	Automatically adjusts display backlight
Motion Sensor	eCompass, 3-axis Gyro, 3-axis accelerometer
DATA CAPTURE	
Scanning	SimulScan simultaneously captures and processes multimedia formatted information in a single step. SE4750SR imager (ID/2D)
Camera	Rear — 8 MP autofocus; f/2.4 aperture; Front — 1.3 MP fixed focus
NFC	ISO 14443 Type A & B, FeliCa, and ISO 15963 cards. Secure NFC via SAM supporting Mifare, Calypso and FeliCa. P2P mode and Card Emulation via UICC and Host.
WIRELESS WAN DATA AND VOICE COMMUNICATIONS	
Radio Frequency Band	Worldwide: LTE: 800/850/900/1800/2100/2600 (FDD 20,5,8,3,1,7) UMTS/HSPA/HSPA+:

850/900/1800/1900

EDGE: 850/900/1800/1900

IEEE® 802.11a/b/g/n/d/h/i/k/r

5GHz: 802.11a/n up to 150 Mbps;

2.4GHz: 802.11b/g/n

- up to 72.2 Mbps

GPS (A-GPS), Navstar, GLONASS

Americas:

GPS

Radio

Data Rates

WIRELESS LAN

850/900/1900/2100 GSM/GPRS/EDGE: LTE: 700/850/1900/AWS/2100 (FDD 17,5,2,4,1) UMTS/HSPA/HSPA+: 850, 900, AWS, 1900, 2100 GSM/GPRS/ Integrated, Autonomous, Assisted

WIRELESS LAN (CONTINUED)		
Operating Channels	Chan 36 - 165 (5180 - 5825 MHz); Chan 1 - 13 (2412 - 2472 MHz); Actual operating channels/ frequencies depend on regulatory rules and certification agency	
Security and Encryption	WEP (40 or 104 bit); WPAWPA2 Personal (TKIP, and AES); WPAWPA2 Enterprise (TKIP, and AES) — EAP-TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC, EAP Fast and LEAP SAM, WPS, Data at rest	
Features	Wi-Fi Multimedia™ (WMM), Soft AP, WiFi Direct	
Certifications	WFA (802.11n, WMM), Cisco CCXv4, Wi-Fi	
Fast Roam	PMKID caching, Cisco CCKM, 802.11r, OKC	
WIRELESS PAN		
Bluetooth	Class 2, Bluetooth v4.0 (Bluetooth® Smart technology)	
DEDIBLIEDALCA	ND ACCECCODIEC	

PERIPHERALS AND ACCESSORIES

Accessories include: 2-slot, 5-slot charge-only and USB/Ethernet ShareCradles, spare battery chargers, MSR, trigger handle, soft and rigid holster, charge-only vehicle cradles, audio solutions and more. For a complete list of accessories, please visit the Zebra product page.

ADDITIONAL MOBILITY DNA SOLUTIONS

Stage Now: Easily stage a handful or hundreds of Android devices by scanning a bar code or tapping an NFC tag.

Enterprise Browser: Next-generation industrial browser to migrate legacy web-based apps or easily

create new apps with todays' highly-graphical and intuitive user interfaces **EMDK:** Created to complement Google's Software Development Kit for Android, Zebra's EMDK provides

a comprehensive toolkit to make it easy to integrate all the functions in our enterprise-class Android devices, from bar code scanning to payment processing.

AppGallery: Zebra's Android enterprise app store makes it easy to find, deploy and manage ready-to-use business apps on any Zebra Android device.

REGULATORY

Visit www.zebra.com/tc75 for regulatory information

WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the TC75 is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, please visit: http://www.zebra.com/warranty

SERVICES

Service from the Start with Comprehensive Coverage: A unique service that covers normal wear and tear as well as accidental damage to internal and external components.

