



The economical, entry-level cart that slashes wasted motion and pays for itself in no time

The entry-level EcoCart mobile powered workstation is designed to provide true mobility within a facility, while eliminating unnecessary movement, touches and transportation wastes. This can result in improved dock to stock cycle times in receiving and on-time shipments in your shipping areas.

This lightweight, compact unit is ideal for powering a laptop, barcode printer and scanner for 8+ hours at time.

Outstanding benefits

- > Reduce labor by as much as \$10K per worker
- Increase receipts by as much as 60%
- > Reduce improperly labeled products
- > Reduce inaccurate inventories
- > Process goods directly at the pallet or on the dock
- → See your ROI in less than three months

Newcastle EC Series Powered Industrial Carts





EC Series with PowerSwap Nucleus® MINI power system (includes stand-alone charging station)



EC Series with SLA power system



Simply swap with a fully charged pack in seconds



Easily integrate a wide variety of accessories



Optional slide-out printer tray



Easy-access power strip (for SLA & fixed lithium

Height Adjustable:

Shelf:

Capacity:

Casters:

Color & Construction:

Model Configurations:

Typical Devices
Powered for 8 Hour Shift:

Battery Type:

Continuous Output Power (W):

Surge Power:

Battery Bank (Wh):

Charge Time (Hrs):

Operating Temp (F):

Weight:

Dimensions:

Middle shelf adjustable from 20-32" (508-813 mm)

(1 standard top shelf) 21.75" wide \times 20" deep metal (552 \times 508 mm) (optional middle shelf) 20" wide \times 20" deep metal (508 \times 508 mm)

60 lbs (27 kg) per shelf evenly distributed

5 x 2" (127 x 51 mm) rubber wheels, front fixed, rear locking swivel

Black powder coat & steel

EC102NU2M	EC350	EC380	EC380-LI
Laptop or small thermal printer & scanner	Laptop/thin client, small thermal printer & scanner	Laptop/thin client, LCD, small or mid- range thermal printer & scanner	
Swappable Lithium Iron Phosphate	Sealed Lead Acid		Fixed Lithium Iron Phosphate
120	450	450	450
300	900	900	900
230	480	1200	960
2.5	4	9	7.5
50-104°	32-95°		50-95°
65.5 lbs (30 kg)	110 lbs. (50 kg)	136 lbs. (62 kg)	90 lbs. (41 kg)

20" long x 21.75" wide x 43" high (508 x 552 x 1092 mm)

