



The Next Generation is Here



Enterprise Class Radio

Rugged, Bright-White Backlit Display

Wear-Resistant Keypad

Built-In Terminal Emulation Clients

The Triton comes with built-in TE clients for VT100/220, TN5250 and TN3270.

Multiple Barcode Scanning Options

Choose options such as Auto-Ranging 1D Laser or 2D Imaging.

Optional "Pistol-Grip" Handle

The Triton can be configured with an optional handle for scan-intensive environments.

Just like all AML products, the AML Triton is Made in the USA. Since 1983, AML has engineered, manufactured, and supported our products in Euless, TX.



Triton



Physical Specs

| Dimensions (without handle) | 225 mm L x 89 mm W x 57 mm D (8.9" L x 3.5" W x 2.3" D) |
|--------------------------------|--|
| Dimensions (with handle) | 225 mm L x 89 mm W x 208 mm D (8.9" L x 3.5" W x 8.2" D) |
| Weight (without handle) | 482g / 17 oz. |
| Weight (with handle) | 709g / 25 oz. |
| Display | 160 x 160 pixel Grayscale LCD with LED Bright White Backlight |
| Battery | Rechargeable 7.2V Lithium-Ion 2600 mAh, 19.2 watt-hours |
| Keypad | 55-key alphanumeric or 35-key numeric |
| Pistol-Grip | Optional (Use M7501-XXXX-XX Part number) |

Wired Data Communications

USB Type B (Slave);

Serial RS-232 (max. rate 115200 baud)

Software Tools

| Terminal Emulation | VT100/102; VT220; TN5250; SSH |
|--------------------|--|
| Utilities | Calculator; Bar Code Data Viewer; Linux Console; |
| Servers | TELNET; FTP; SSH/SFTP; HTTP |

Performance Specs

| Processor | Samsung® S3C2410 @ 202 MHz |
|--------------------------------|---|
| Operating Platform | AML Embedded Linux® OS; Linux® Kernel 2.6.39 |
| Memory (RAM/ROM) | 32 MB SDRAM; 16 MB Non-volatile NOR Flash |
| Integrated Scanning Options | Standard 1D Laser; Lorax "Near/Far" Laser; 2D Imager |
| Development Environment | AML M7220 SDK for Linux® supporting C and C++; GNU GCC 3.3.5 for ARM-Linux®; Fully Open Sourced Licensing |

Optional Peripherals & Accessories

Triton communication and charging cradle (Red)
Single slot communication and charging cradle
Four slot terminal charger
Four slot battery charger
Vehicle mount terminal charger
Vehicle mount cradle (non-charging)
Holster with adjustable belt

Wireless Data Communicatons

| WLAN | IEEE 802.11b/g/n (Summit SDC-MSD40NBT) |
|------------|--|
| | SUMMIT DATA COMMUNICATIONS |
| Security | Wireless Equivalent Privacy (WEP); Wi-Fi Protected Access (WPA); IEEE 802.11i (WPA2) |
| Encryption | WEP; TKIP; AES |
| Antenna | Internal Dual-band Diversity |

Environmental Specs

| Drop Specifications | 5' (1.5M) to concrete |
|----------------------------------|--------------------------------------|
| Operating Temp | -10° to 50°C / 14° to 122°F |
| Storage Temp | -25° to 50°C / -13° to 122°F |
| Humidity | 5% to 90% RH, non-condensing |
| Electrostatic Discharge (EDS) | 15kVDC air; 4kVDC contact, all sides |
| Sealing | IP51 (dust, drip waterproof) |

Regulatory Specs

| EMI/RFI | FCC Part 15 Class A |
|---------------------------------------|-------------------------------|
| Laser Safety (if equipped) | CDRH Class II; IEC Class 2 |
| Restrictions of Hazardous Material | EU RoHS Compliant / Pb Free |

Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.

Specifications are subject to change without notice. All names and products are the trademarks or registered trademarks of their respective organizations.



Corporate Headquarters 2190 Regal Parkway Euless, Texas 76040

Sales & Customer Service Tel: 800-648-4452 Fax: 817-685-6232 Email: sales@amltd.com www.amltd.com www.amlkiosks.com Local: 817-571-9015 Fax: 817-571-6176

Technical Support Tel: 877-842-3990 Fax: 817-685-6232 Email: support@amltd.com



