

ECONOMIC



4 inch Barcode Label Printer SRP-770II



All-in-one



BIXOLON SRP-770II is the first label printer developed with the technological power of Samsung, which has been proved in the POS printer market. The SRP-770II can print 5 ips (127 mm/sec) and can recognize various programming languages such as SLCS, BPL-Z™, BPL-E™ automatically, and also the width of the paper can be adjusted easily to the range of 1.5~4.2 inch so that it can be used for barcode printing as well as receipt printing. The various on-board interfaces including Serial, Parallel, and USB allow flexible system configuration.

BR-SRP-770II-EN-AUG14

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

PRINT CHARACTERISTICS

Print Method: Direct Thermal

Print Speed: Up to 5 ips (127 mm/s)

Print Resolution: 203 dpi

Print Width: Up to 104 mm

Print Length: 6 ~ 304 mm

Media Sensor: Transmissive, Reflective, Head open

MEDIA CHARACTERISTICS

Media Type: Gap, Black Mark, Notch, Continuous, Fan-Fold

Media Width: 42 ~ 106 mm

Media Roll Diameter: Up to 130 mm

Media Roll Diameter: 0.06 ~ 0.20 mm

Supply Method: Easy Paper Loading

PHYSICAL CHARACTERISTICS

Dimensions (W x L x H): 184 x 221 x 171 mm
(7.24 x 8.70 x 6.73 inch)

Weight: 1.65 kg (3.63 lbs.)

Power: External Power Adaptor 100-240V AC, 50/60Hz

PERFORMANCE CHARACTERISTICS

Memory: 512KB SDRAM, 2MB FlashROM

Interface: Triple Interface

USB V1.1 FS + Serial + Parallel

ENVIRONMENT CHARACTERISTICS

Temperature: Operating: 0 ~ 40°C (32 ~ 104°F)
Storage: -20 ~ 60°C (-4 ~ 140°F)

Humidity: Operating: 10 ~ 80% RH
Storage: 10 ~ 90% RH

SOFTWARE

Emulation: SLCS, BPL-Z™, BPL-E™

Driver: Windows Driver, Linux CUPS Driver, Mac Driver,
Virtual COM USB Driver, Utility Program, Label Artist™

SDK: Android SDK

FONTS / GRAPHICS / SYMBOLOGIES

Fonts: • 10 SLCS Resident Bitmap Fonts
• One SLCS Resident Scalable Font
• 23 Code Page

Graphics: Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbologies: 1D: Coda Bar, Code39, Code93, EAN-8, EAN-13,
Interleaved 2-of-5, ITF, UCC/EAN-128, UPC-A,
UPC-E

2D: Data Matrix, MaxiCode, PDF417, QR Code
(select two only)

OPTIONS

Optional: Auto Cutter

BIXOLON®

www.bixolon.com



BIXOLON Co., Ltd.

7~8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de