

# Duratherm Receipt



- Duratherm Receipt is simple to use and does not require the use of a ribbon.
- Duratherm Receipt products are coated with a heat-sensitive layer which is imaged through direct contact with the Printhead. The result is a pattern of black dots forming text, bar codes, or graphics.
- Available products range from an economical low-caliper paper receipt to a high-performance film receipt with enhanced durability.

Intermec's Duratherm Receipt portfolio represents a range of products that match performance to specific application needs, providing the right product for the job every time.

Duratherm receipt products offer high-quality, cost-effective printing with several levels of durability from uncoated paper receipts to top-coated film receipts. Without the need for ribbon changeover, Duratherm products require less operator intervention and training.

## **Better Together**

The Intermec media solution has added advantages when paired with Intermec printers:

- Co-engineered printers and media ensure consistent print quality and performance
- Thermal transfer printability allows on-demand generation of durable labels, eliminating high cost and inventory obsolescence associated with preprinting

## Duratherm Receipt Portfolio

Product	Description	Image Life*	Recommended Applications	Recommended Heat Setting
<b>Duratherm II Receipt</b>	A 2.5-mil non-top-coated paper receipt that provides excellent print quality.	10 Years	Well suited for most general receipt applications, such as retail, coupon, Point Of Sale (POS), and light-weight ticketing.	IPL: 101 Const/Factor: 30/40
<b>Duratherm III Receipt</b>	A 3-mil top-coated paper receipt that delivers high quality printing an enhanced durability.	20 Years	Duratherm III receipt is recommended for applications where high humidity, moisture contact, and surface abrasion are a concern.	IPL: 401 Const/Factor: 45/40
<b>Duratherm S Receipt</b>	A three-mil synthetic polyolefin receipt that provides excellent print quality and enhanced durability as compared to paper products.	15 Years	Duratherm S Receipt is recommended for use in wet environments where chemical contact is not a concern.	IPL: 430 Const/Factor: 80/40

\*Image life is based upon the proper storage of the printed receipt in a light-free environment, protected from chemical exposure at 70°F/50%RH.

### North America

#### Corporate Headquarters

6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348-2600  
Fax: (425) 355-9551

#### North Latin America

##### Headquarters Office

Mexico  
Phone: +52 55 52-41-48-00  
Fax: +52 55 52-11-81-21

### South Latin America

#### Headquarters Office

Brazil  
Phone: +55 11 5502.6770  
Fax: +55 11 5502.6780

### Europe/Middle East &

#### Africa Headquarters Office

Reading, United Kingdom  
Phone: +44 118 923 0800  
Fax: +44 118 923 0801

### Asia Pacific

#### Headquarters Office

Singapore  
Phone: +65 6303 2100  
Fax: +65 6303 2199

### Internet

www.intermec.com  
Worldwide Locations:  
www.intermec.com/locations

### Sales

Toll Free NA: (800) 934-3163  
Toll in NA: (425) 348-2726  
Freephone ROW:  
00 800 4488 8844  
Toll ROW: +44 134 435 0296

### OEM Sales

Phone: (425) 348-2762

### Media Sales

Phone: (513) 874-5882

### Customer Service and Support

Toll Free NA: (800) 755-5505  
Toll in NA: (425) 356-1799

Copyright © 2011 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 612116-01A 03/11

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

