

Motorola CS3000 Series

1D Laser Scanning Device



FEATURES

Flexible mobile 1D laser scanner

A mobile bar code scanner with two modes of operation: batch for uploading data to a host at a later time or real-time capture and transmission to a host application via a wireless Bluetooth connection to smartphones, PDAs and laptops

Long battery life

A 24-hour batch/12-hour Bluetooth mode battery life insures well over single shift scanning performance on a charge

Simple two button design

Easy to hold and use — almost no training required

Small and lightweight

Fits in a pocket or on a neck lanyard and weighs only 2.45 oz./70 gm

Easy to integrate with a host device

Batch USB connectivity or wireless Bluetooth enables compatibility with virtually any host device

Enable anywhere anytime cost-effective mobile 1D laser scanning

The innovative Motorola CS3000 Series enables enterprises to easily implement 1D laser scanning where either mobility or the cost and size of a traditional scanning device is an inhibitor. The tiny device is affordably priced and fits in a pocket or on a lanyard. The CS3000 can be utilized in standalone mode for the batch scanning of bar codes, while the CS3070 offers batch mode as well as real-time bar code data transmission to a host application via a wireless Bluetooth® connection to smartphones, laptops and more. Managing the data in batch mode is easy. Once connected to a host, the batch data can be configured for automatic transfer to an application. Since captured scans are placed in a user-definable standard ASCII file type, the information can be easily utilized to populate order forms, spreadsheets and inventory lists. The result is a new level of affordability for 1D scanning - and the ability to streamline, error proof and simplify more business processes.

Motorola signature ergonomics ensure user comfort and ease of use

The easy to use CS3000 Series requires virtually no training to operate. The highly intuitive simple 2-button interface makes scanning easy. In addition, grooves that guide hand and fingers into the most comfortable scanning position combine with soft rubber trigger buttons to bring comfort to the most scan intensive tasks.

Enterprise class capacity, reliability and total cost of ownership (TCO)

The large memory capacity allows workers to capture over a million bar codes, providing ample support for the largest batch operations. The non-volatile memory ensures that batch data is retained. Built-in business durability provides a low TCO. IP40 sealing, a 4 ft./1.2 m drop specification and the ability to survive 500 1.64 ft./ 0.5 m consecutive tumbles combine to ensure dependable operation. And a 24-hour batch/12-hour Bluetooth mode battery cycle time insures well over single shift scanning performance on a charge.

Best-in-class high performance scanning

The integrated SE955 scan engine delivers Motorola's world-renowned scanning quality and reliability. The wide working range provides extraordinary application flexibility, allowing users to capture bar codes from near contact to as far as 45 in./114.3 cm away, in virtually any lighting condition. Aggressive performance enables the capture of even damaged and poor quality bar codes. And a time stamp can be automatically appended to each batch scan, providing additional business intelligence.

SPECIFICATION SHEET

MOTOROLA CS3000 SERIES 1D Laser Scanning Device

512 MB nonvolatile memory

Provides the capacity to store over a million scans and ensures the data is retained — ideal for virtually any batch operation

Superior scanning performance

Easy and intuitive to use just point, click and scan; enables easy capture of even dirty, damaged and poor quality bar codes

Enterprise durability: 4 ft./1.2 m drop specification; 250 tumbles (500 drops) @ 1.64 ft./0.5 m; IP40 sealing Ensures reliable operation despite the inevitable drops and bumps in real world use

APPLICATIONS

Supply Chain Proof of Delivery (PoD);

Customer Managed Inventory (CMI)

Facilities Management Inspections;

Asset Tracking

Field Sales

Merchandising; Account Management; Delivery

Retail

Inventory; Gift Registry

Automate your workflow with two flexible operational modes — batch and real time

In batch mode, this pocket friendly device allows guards and custodial staff to scan bar codes on entry doors and other locations, and upload the time and date stamped data at the end of a shift to document the accurate completion of activities. Outside the enterprise, manufacturers and distributors can provide customers with a CS3000 to scan inventory as it is used, effectively automating the ordering process at the point of consumption. In real-time mode, the Bluetooth enabled CS3070 can be paired with virtually any existing smartphone, allowing route drivers to easily scan the items in a delivery or on the store shelves to help automate and error proof the delivery and ordering process.

For more information on how you can put the CS3000 Series to work in your organization, please visit us on the web at www.motorola.com/CS3000 or access our global contact directory at www.motorola.com/enterprisemobility/contactus

CS3000 Series Specifications

Physical Characteristics		
Dimensions:	3.41 in. L x 1.95 in. W x .87 in. H 8.65 cm L x 4.95 cm W x 2.2 cm H	
Weight:	With batteries: 2.45 oz./70 gm	
Scan Engine:	SE955 laser, single line laser	
Memory:	512MB Flash	
Memory Capacity:	Over 1 million barcodes (UPC with time date stamp)	
LEDs:	Scan LED (Green, Red, and Amber) and Bluetooth® LED (Blue)	
Buttons:	Scan, remove scan (batch mode only), enable Bluetooth (RF scanners only)	
Operating Modes		
Batch:	Scans recorded with optional time/date stamp	
Open Bluetooth:	Real time wireless data transmission	
Battery		
Battery:	780 mAh Lithium ion	
Charge Time:	3 hours	
Battery Life:	Batch - 24 hours use or 8,500 scans (6 scans per minute on full charge) Standby - 3 months Bluetooth - 12 hours use or 4,250 scans (6 scans per minute on full charge)	
Power Consumption:	5V, 500mA max while charging	
Performance Characte	ristics	
Decode Capability:	1D symbologies	
Interfaces Supported:	USB (Mini jack): CS3000 and CS3070 Bluetooth: CS3070	
Real Time Clock:	A date/time stamp can be recorded with each bar code scanned (Batch mode operation only)	
Batch Communication:	USB 2.0	

Bluetooth	
Bluetooth Radio:	Bluetooth, Class 2, Version 2.1 + Enhanced Data Rate (EDR)
Bluetooth Range:	30 ft./10 m
Bluetooth Profiles:	HID keyboard wedge and Serial Port Profile (SPP)
User Environment	
Drop Specification:	4 ft./1.21 m drop to tiled linoleum over concrete, 6 drops per 6 sides, across the operating temperature range
Tumble Specification:	250 cycles @ 1.64 ft./0.5 m (500 drops)
Operating Temperature:	32° to 104° F /0° to 40° C
Storage Temperature:	-40° to 158° F /-40° to 70°C
Environmental Sealing:	IP40
Humidity:	10 to 95% noncondensing
Regulatory	
Laser Safety:	EN 60825-1, IEC 60825-1, 21CFR1040.10
EMC:	CS3000: FCC Part 15 Class B, ICES 003 Class B, EN 55022, EN 55024 CS3070: FCC Part 15 Class B, ICES 003 Class B, EN 55022, EN 55024, EN 301 489-1, EN 301 489-17
Radio:	CS3070: EN 300 328
Electrical Safety:	UL 60950-1, C22.2 No. 60950-1, EN 60950-1, IEC 60950-1
Environmental:	RoHS Directive 2002/95/EEC
Warranty	
Warranted against defects in	workmanship and materials for a period of twelve (12) months
Services	
Service from the Start Advan	ce Exchange Support





motorola.com

Part number SS-CS3000. Printed in USA 05/10. MOTOROLA and the Stylized M Logo and SYMBOL and the Stylized SYMBOL Logo are registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. ©2010 Motorola, Inc. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.